

Serial No.: 10/549,567
Atty. Docket No.: P70821US0

IN THE CLAIMS:

Please amend the claims as follows:

1. (Currently Amended) An ostomy appliance comprising:

a base plate, said base plate having a first hole for receiving a stoma, ureter, or catheter and an adhesive wafer having a first surface to be attached to the wearer's abdomen, back, or chest;

a receiving ~~member or bag~~ releasably and reattachably attached to the base plate, said receiving bag having a second hole for receiving wastes exiting the stoma, ureter or catheter and a receiving bag bottom portion which defines a distal-most part of said receiving bag relative to ~~that is most distal from~~ said second hole; and

a disposable inner bag liner forming a second bag inside the receiving ~~member bag~~ bag and being releasably attachable and reattachable to the base plate in a first coupling area by a first coupling component, said disposable inner bag liner having a third hole for receiving wastes exiting the stoma, ureter or catheter and the receiving ~~member bag~~ bag being releasably and reattachably attachable to the base plate by a second coupling component, the first coupling component being in the form of an adhesive flange

Serial No.: 10/549,567
Atty. Docket No.: P70821US0

projecting from the rim of the third hole and having a surface for releasable sealing against a second surface of the base plate facing away from the user, ~~and~~ said inner bag liner having folds along a plurality of folding lines such that said inner bag liner is compacted lengthwise prior to use, said folds being provided between the third hole and an inner bag liner bottom portion which defines a distal-most part of the inner bag liner relative to the third hole both when the inner bag liner is folded and when the inner bag liner is fully unfolded inside the receiving bag to reach a distal-most position relative to said third hole ~~a bottom of the inner liner~~ so that, when the bag is empty and in said compacted condition, said inner bag liner bottom portion is in a folded position adjacent said third hole such that ~~and distal from said receiving member bottom portion,~~ initial wastes exiting the stoma, ureter or catheter will push ~~pushing~~ against said inner bag liner bottom portion thus ~~and~~ causing said folds to unfold so that said inner bag liner bottom portion moves away from said folded position adjacent the third hole to a said distal-most position relative to said third hole ~~most distal from the stoma, ureter or catheter and adjacent the bottom portion of said receiving member as the inner bag liner is filled.~~

Serial No.: 10/549,567
Atty. Docket No.: P70821US0

2. (Currently Amended) The ostomy appliance as claimed in claim 1 wherein the second coupling component is in the form of an adhesive flange projecting from the rim of the second hole and having a surface for adhesive sealing against the second surface of the base plate, said first and second coupling components being configured to allow the inner bag liner to be removed and replaced with a new inner bag liner while reusing the receiving bag.

3. (Previously Presented) The ostomy appliance as claimed in claim 2 wherein an outer diameter of the first coupling component is greater than an inner diameter of the second coupling component.

4. (Currently Amended) The ostomy appliance as claimed in claim 2 wherein a peel strength of the adhesive sealing of the first coupling component is greater than a peel strength of the second ~~couplings~~ coupling component.

5. (Previously Presented) The ostomy appliance as claimed in claim 1 wherein the second coupling component is in the form of one or more coupling rings and wherein an outer diameter of the first coupling component is smaller than an inner diameter of the second coupling component.

Serial No.: 10/549,567
Atty. Docket No.: P70821US0

6. (Previously Presented) The ostomy appliance as claimed in claim 1 wherein the inner bag liner is provided with a membrane allowing intestinal gas to escape but is impermeable to liquids.

7. (Currently Amended) An ostomy appliance comprising:

an adhesive wafer, said adhesive wafer having a first hole for receiving a stoma, ureter, or catheter, said adhesive wafer having a first surface to be attached to the wearer's abdomen, back, or chest; ~~and~~

a receiving ~~member or~~ bag attached to the adhesive wafer, said receiving bag having a second hole for receiving wastes exiting the stoma, ureter or catheter and a receiving bag bottom portion which defines a distal-most part of the receiving bag relative to that is most distal from said second hole; and

a disposable inner bag liner forming a second bag inside the receiving ~~member~~ bag and being releasably and reattachably attachable to the adhesive wafer by a ~~first~~-coupling component, said disposable inner bag liner having a third hole for receiving wastes exiting the stoma, ureter or catheter, said ~~first~~-coupling component being in the form of an adhesive flange projecting from the rim of the third hole and having a surface for releasable and reattachable sealing against a first surface of the adhesive wafer,

Serial No.: 10/549,567
Atty. Docket No.: P70821US0

and said inner bag liner having folds along folding lines such that said inner bag liner is compacted lengthwise prior to use, said folds being provided between the third hole and an inner bag liner a bottom portion which defines a distal-most part of the inner bag liner relative to the third hole both when the inner bag liner is folded and when said inner bag liner is fully unfolded inside the receiving bag to reach a distal-most position relative to said third hole of the inner liner so that, when the inner bag liner is empty and in said compacted condition, said inner bag liner bottom portion is in a folded position adjacent said third hole such that ~~and distal from said receiving member bottom portion,~~ initial wastes exiting the stoma, ureter or catheter will push ~~pushing~~ against said inner bag liner bottom portion thus ~~and~~ causing the folds to unfold so that said inner bag liner bottom portion moves away from said folded position adjacent the third hole to said distal-most position relative to said third hole ~~a position most distal from the stoma, ureter or catheter and adjacent the bottom portion of said receiving member~~ as the liner is filled.

8. (Previously Presented) The ostomy appliance as claimed in claim 1 wherein the inner bag liner when compacted lengthwise forms

Serial No.: 10/549,567
Atty. Docket No.: P70821US0

a disc-like structure having an outer diameter less than the inner diameter of the first coupling component.

9. (Previously Presented) The ostomy appliance as claimed in claim 1 wherein the folding of said liner along said folding lines forms a bellows.

10. (Previously Presented) The ostomy appliance as claimed in claim 1 wherein the folding of said liner along said folding lines forms a telescopic bellows.

11. (Previously Presented) The ostomy appliance as claimed in claim 1 wherein the closed end of the compacted inner bag liner is provided with a cover to retain said inner bag liner in said compact condition prior to use.

12. (Currently Amended) A disposable inner bag liner having an open end for receiving effluents or waste products of the body and for use together with an ostomy appliance having an adhesive wafer to be attached to the wearer's abdomen, back, or chest and a receiving ~~member or bag~~ having a receiving bag ~~member~~ hole for receiving wastes exiting the stoma, ureter or catheter, said

Serial No.: 10/549,567
Atty. Docket No.: P70821US0

disposable inner bag liner comprising a liner hole in said open end for receiving wastes exiting the stoma, ureter or catheter and having a closed end being capable of forming a bag inside the receiving ~~bag member~~, an adhesive flange projecting from the rim of the liner hole and having a surface for releasable sealing against a surface of the adhesive wafer, said inner bag liner having folds along folding lines such that said inner bag liner is compacted lengthwise prior to use, said folds being provided between the liner hole and an inner bag liner a bottom portion which defines a distal-most part of the inner bag liner relative to said liner hole both when the inner bag liner is folded and when said inner bag liner is fully unfolded inside the receiving bag to reach a distal-most position relative to said liner hole ~~of said inner liner so~~ that, when the inner bag liner is empty and in said compacted condition, said inner bag liner bottom portion is in a folded position adjacent said liner hole such that ~~and distal from said receiving member bottom portion,~~ initial wastes exiting the stoma, ureter or catheter will push ~~pushing against~~ said inner bag liner bottom portion thus ~~and~~ causing said folds to unfold so that said inner bag liner bottom portion moves away from said folded position adjacent the liner hole to a said distal-most position relative to said liner hole ~~most distal from the stoma, ureter or catheter and~~

Serial No.: 10/549,567
Atty. Docket No.: P70821US0

~~adjacent the bottom portion of said receiving member as the liner~~
is filled.

13. (Previously Presented) The disposable inner bag liner as claimed in claim 12 wherein the inner bag liner is provided with a membrane allowing intestinal gas to escape from the inner bag liner but is impermeable to liquids.

14. (Currently Amended) A method of applying to an ostomate an ostomy appliance comprising a base plate, said base plate having a first hole for receiving a stoma, ureter, or catheter and an adhesive wafer having a first surface to be attached to the wearer's abdomen, back, or chest; a receiving ~~member or bag~~ releasably and reattachably attachable to the base plate, said receiving ~~member bag~~ having a second hole for receiving wastes exiting the stoma, ureter or catheter and a receiving bag bottom portion which defines a distal-most part of the receiving bag relative to most distal from said second hole; and a disposable inner bag liner forming a second bag inside the receiving ~~member bag~~ and being releasably and reattachably attachable to the base plate, said disposable inner bag liner having a third hole for receiving wastes exiting the stoma, ureter or catheter, said inner

Serial No.: 10/549,567
Atty. Docket No.: P70821US0

bag liner being compacted lengthwise by folds along folding lines to form a disc-like structure, said folds being provided between said third hole and ~~a~~ an inner bag liner bottom portion which defines a distal-most part of the inner bag liner relative to the third hole both when the inner bag liner is folded and when said inner bag liner is fully infolded inside the receiving bag to reach a distal-most position relative to said third hole ~~of said inner bag liner~~ so that, when the inner bag liner is empty and in said compacted condition, said inner bag liner bottom portion is in a folded position ~~is~~ adjacent said third hole such that ~~and distal from said receiving member bottom portion,~~ initial wastes exiting the stoma, ureter or catheter will push ~~pushing~~ against said inner bag liner bottom portion ~~and~~ causing said folds to unfold so that said inner bag liner bottom portion moves away from said folded position adjacent the third hole to said distal-most ~~a position most distal from the stoma, ureter or catheter and adjacent the bottom portion of said receiving member~~ as the liner is filled, said inner bag liner being releasably and reattachably attachable ~~releasably~~ to the base plate in a first coupling area by a first coupling component and the receiving member ~~bag~~ being releasably and reattachably attachable ~~releasably~~ to the base plate by a second coupling component, said first coupling component being in

Serial No.: 10/549,567
Atty. Docket No.: P70821US0

the form of an adhesive flange projecting from the rim of the third hole and having a surface for adhesive sealing against a second surface of the base plate facing away from the user, said method comprising:

locating the stoma and applying the base plate;

locating the inner bag liner and applying and sealing the same to the first coupling area;

removing a release liner covering said first coupling component; and

attaching the receiving member to the base plate.

15. (Currently Amended) The method as set forth in claim 14, further comprising the step of securing said inner bag liner ~~disc-like structure~~ in said compact conformation by placing a cover on a closed end of said inner bag liner, said cover being removed in use of said inner bag liner by automatic unfolding of said bag liner in response to receipt of waste exiting said stoma, ureter or catheter ~~and~~ entering said third hole of said inner bag liner.

16. (Currently Amended) The ostomy appliance as claimed in claim 8 further comprising a cover on a ~~the~~ closed end of said

Serial No.: 10/549,567
Atty. Docket No.: P70821US0

inner bag liner ~~disc-like structure~~ to retain said inner bag liner in said compact condition prior to use.

17. (Previously Presented) The disposable inner bag liner as claimed in claim 12 wherein the closed end of the compacted inner bag liner is provided with a cover that retains said inner bag liner in said compact condition prior to use.

18. (Withdrawn) The disposable inner bag liner as claimed in claim 12 wherein said inner bag liner is folded radially and longitudinally to form a combination bellows.